

Quality Guarantee

Mounting board 015 - light white, multiple ply (thicknesses: 0.75/1.5/2.6/3.0 mm)



We hereby confirm that our "Mounting board 015 - light white, multiple ply (thicknesses: 0.75/1.5/2.6/3.0 mm)" fulfils the following characteristics:

Board

- 100 % bleached cellulose
- Without the usage of recycling fibres
- Free of wooden fibres
- Kappa level 1 - 2 = lignin-free
- pH 7.5 - 10.0 = acid-free (in accordance with ISO 6588-1:2005)
- Alkaline buffer > 3 % natural calcium carbonate (GCC)
- Sizing: neutral/synthetic (without alum additive)
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

Glue used for lamination

- Dispersion glue free of solvents and plasticizers (softening agents)
- pH approx. 7.0
- Photographic Activity Test (PAT) passed in accordance with ISO 18916:2007

This quality corresponds to the technological basis of the following standards:

DIN EN ISO 9706

Information and documentation - Paper for documents - Requirements for permanence

ANSI/ NISO Z.39.48

American National Standard for Permanence of Paper for Publications and Documents in Libraries and Archives

DIN 6738:2007

Highest level of permanency LDK 24-85

We guarantee legally binding that the above stated material meets the above mentioned characteristics.

The material is ageing resistant and provides active protection for the artefact.

KLUG-CONSERVATION May 2016



Maren Negendank

Quality Assurance